

# An affordable ATM with the versatility to enhance your cardholder's experience.

Triton's PC platform RL5000<sup>xP</sup> is changing the way people think about ATMs. The all-new model offers a stunning 10.4 inch LCD display and supports a long list of value-added transactions. All at a much lower price point than other PC-based machines.

Furthermore, Triton's Prism™ ATM software provides financial institutions with a simple HTML interface for customized screen content.

This revolutionary configuration offers vendor independence through the XFS specification and makes possible a long list of revenue generating value-added services.

But what makes the Triton RL5000<sup>NP</sup> most popular with banks and credit unions is that it meets all regulatory requirements at half the cost. The PC-based RL5000<sup>NP</sup> includes a Visa Encrypting PIN Pad (VEPP) and Triple DES compliance.

In addition to its low price, the RL5000<sup>xp</sup> also offers an extremely low cost of operation. The wide range of dispensers available offers customers the ability to choose the capacity that most matches their usage.

There's not another PC ATM on the market that offers the level of performance and cost-competitiveness delivered by the Triton RL5000<sup>№</sup>. The future of ATMs is here.






Triton Headquarters • 522 East Railroad Street Long Beach, Mississippi 39560 USA With offices throughout the U.S. and worldwide including Canada, UK, Australia, and Hong Kong Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191 www.triton.com • Email: sales@triton.com

© 2007 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.

Current as of 04/07 · RL5000xp product sheet-07203-00127



The dimensions shown comply with U.S. Federal ADA guidelines. For installation within the U.S., be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.

\*specifications subject to change without notice

ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE

## The future of ATMs is here.

RL5000<sup>xp</sup>

### FEATURES:

- · Two to four cassettes
- 80 mm thermal printer with presenter
- Dip-style card reader; optional dip EMV smart card reader / encoder, EMV motorized card reader (Track 1,2,3 Read) or EMV motorized card reader (Track 1,2,3 Read, Track 3 Write)
- Audio transactions for the visually impaired
- Visa Encrypting PIN Pad (VEPP) to comply with all international encryption standards, Triple DES compliant, optional metal VEPP
- UL 291 Business Hours cabinet or optional UL 291 Level 1 Safe (up to 700 lb, 318 kg)
- Electronic lock or optional Kaba Mas Cencon lock
- Multi-lingual capabilities
- TCP/IP communications
- Dimensions:
- · Width 16.9" (429 mm)
- · Depth 32.33" (821 mm)
- Height:
  - · 54.3" (1379 mm) without topper
  - · 69.9" (1648 mm) with mid-topper
  - · 77.8" (1976 mm) with high-topper
- Weight:
  - · 172 lb (78 kg) weight varies with options
- Advertising potential:
  - · Decals and signage
- Couponing
- · Display graphics

#### **OPERATING SYSTEM:**

- Intel® Celeron® or optional Intel Pentium® IV
- Microsoft® Windows® XP

In Detail

- CD-Rom optional with Pentium IV
- Software options:
  - · XFS compliance
  - · Emulation
- 40 GB 3.5" (89 mm) hard drive, expandable
- 256 MB SDRAM, expandable
- 10.4" (264 mm) SVGA color display with 800 x 600 resolution
- Two 32-bit PCI expansion slots, one with PIV

### **OPERATING SPECS:**

- Temperature:
  - · 10° to 35° C / 50° to 95° F
- Relative humidity:
- · 20% to 80% non-condensing
- Power consumption:
  - · 3.0 A @ 120 VAC at 60 Hz
  - · 3.0 A @ 230 VAC at 50 Hz

